

MATERIAL SAFETY DATA SHEET

Date of Issue: 14/01/2008

STATEMENT OF HAZARDOUS NATURE

Not classified as hazardous according to criteria of Work safe Australia.

COMPANY DETAILS

Company Jaegar Australia
Address: 2/9 Tower Crt, Noble Pk 3174
Telephone: (03) 9769-1788
Fax: (03) 9769-0655
Emergency Telephone: 0408 347 425

IDENTIFICATION

PRODUCT NAME: Paint Remover Paste

Other Names:

Manufacturer's Code: PS-106

Un No: 1593

Dangerous Goods Class

& Subsidiary Risk: N/A

Hazchem Code: 2(Z)

Poisons Schedule: S5

Use: Apply by swabbing, brushing and spraying with coarse jet or immersion.

PHYSICAL DESCRIPTION/PROPERTIES

Appearance: Yellow Viscous Gel
Melting Point: N/A
Vapour Pressure: N/A
Specific Gravity: N/A
Flash Point: N/A
Flammability Limits: Non-flammable
Solubility in water: N/A

Other Properties:

Corrosiveness: Not considered corrosive to metals.
PH (1% solution): Not available.

INGREDIENTS

Chemical name and CAS No as defined by the NOHSC Code 1008 list all hazardous substances. Other ingredients which are determined to be non-hazardous are listed by generic name or as "other ingredients determined not to be hazardous".

CHEMICAL NAME	CAS NO	PROPORTION
Methylene Chloride	75-09-2	>70%
Toluol	N/A	<10%
Wetting Agent	N/A	<5%
Thickener	N/A	<5%
Solvent	N/A	<20%

HEALTH HAZARD INFORMATION

Health Effects

Acute:

SWALLOWED: Irritating and nauseating. Can cause irritation to the mouth, throat and gastro intestinal tract.

EYE: Irritating to the eye.

SKIN: Irritating on prolonged contact by defatting the skin.

INHALED: May cause dizziness or headache on prolonged exposure.

CHRONIC: Not applicable.

FIRST AID

SWALLOWED: Contact a doctor or Poisons Information Centre. If help is more than 15 minutes away induce vomiting using Ipecac Syrup (APF).

EYE: If contacted in the eyes or face, remove contact lenses if worn. Hold eye open and flood with plenty of water for at least 15 minutes. Seek medical advice.

SKIN: Remove all contaminated clothing and footwear. Wash effected skin thoroughly with water. Wash any contaminated clothing before re-use.

INHALED: Remove effected person from contaminated area. Apply artificial respiration if not breathing. Urgently seek medical advice.

First Aid Facilities: Fresh water.

PRECAUTIONS FOR USE

EXPOSURE: TLD for Methylene Chloride is 50ppm.

ENGINEERING CONTROLS: Not applicable.

VENTILATION: Sufficient to maintain concentration below TLV.

PERSONAL PROTECTION: Neoprene gloves and safety glasses to be worn at all times when using product.

FLAMMABILITY: Not flammable or combustible

SAFE HANDLING INFORMATION

STORAGE & TRANSPORT: Keep containers tightly closed when product is not in use. Store in a cool dry place.

SPILLS & DISPOSAL: Absorb on vermiculite or similar absorbing material and collect into properly labelled drums. Contact local authorities with regard to correct disposal. Wash area thoroughly with water.

FIRE/EXPLOSION HAZARD: Use water fog, foam or dry agent. Wear breathing apparatus and protective gloves for fire only. Contain. Prevent by any means available the spillage from entering drains or watercourses.

OTHER INFORMATION:

The Peak Limitation quoted above is the Work safe Adopted National Exposure Standard for the maximum or peak airborne concentration over the shortest analytically practicable period of time, which does not exceed 15 minutes.

This MSDS is valid for five years from date of issue but readers should contact Jaegar Australia to ensure that this is the latest issue. As per the Work safe Guidance Note NOHSC 3017, each user should review the information in the specific context of the intended application.

CONTACT POINT: General Manager (0408 347 425)
Office: (03) 9769-1788